

C.3 and C.6 Development Review Checklist

Municipal Regional Stormwater Permit (MRP)
 Stormwater Controls for Development Projects

Applicants: This form should be filled out by the Project Civil Engineer, if one is associated with the project.

Project Information

I.A Enter Project Data (For "C.3 Regulated Projects," data will be reported in the municipality's stormwater Annual Report.)

Project Name:	12400 Skyline Boulevard	Case Number:	
Project Address:	12400 Skyline Boulevard, Woodside CA 94062	Cross Street:	Misty Ridge Road
Project APN:	067-250-030	Project Watershed:	Pilarcitos Creek
Applicant Name:	BKF Engineers	Project Phase No.	
Applicant Phone:	(650)482-6417	Applicant Email Address:	angelhernandez@bkf.com

Development Type: (check all that apply)

<input checked="" type="checkbox"/> Single Family Residential: A stand-alone home that is not part of a larger project.	# of units:	
<input type="checkbox"/> Single Family Residential: Two or more lot residential development. ¹	# of units:	
<input type="checkbox"/> Multi-Family Residential	# of units:	
<input type="checkbox"/> Commercial		
<input type="checkbox"/> Industrial, Manufacturing		
<input type="checkbox"/> Mixed-Use	# of units:	
<input type="checkbox"/> Streets, Roads ² , etc.		
<input type="checkbox"/> Redevelopment ³ as defined by MRP: creating, adding and/or replacing exterior existing impervious surface on a site where past development has occurred.		

I.A.1

<input type="checkbox"/> 'Special land use categories' as defined by MRP: (1) auto service facilities ³ , (2) retail gasoline outlets, (3) restaurants, (4) uncovered parking area (stand-alone or part of a larger project)
<input type="checkbox"/> Institutions: schools, libraries, jails, etc.
<input type="checkbox"/> Parks and trails, camp grounds, other recreational
<input type="checkbox"/> Agricultural, wineries
<input type="checkbox"/> Kennels, Ranches
<input type="checkbox"/> Other, Please specify _____

Project Description (Also note any past or future phases of the project.)⁴

The project proposes to construct a two-story single family residence downhill of the existing cottage. Additional site improvements includes existing driveway improvements for fire access, a courtyard, and associated pathways.

I.A.2 Total Area of Site: 3.1 acres

I.A.3 Total Area of land disturbed during construction : 0.70 acres I.A.4 Site slope: 15%
 (include clearing, grading, excavating and stockpile area)

I.A.5 Certification:

I certify that the information provided on this form is correct and acknowledge that, should the project exceed the amount of new and/or replaced impervious surface provided in this form, the as-built project may be subject to additional improvements.

Preliminary Calculations Attached Final Calculations Attached Stormwater Control Plan Attached

Name of person completing the form:	Angel Hernandez	Title:	Design Engineer
Signature:	<i>Angel Hernandez Mora</i>	Date:	12/19/2022
Phone Number:	(650)482-6417	E-mail:	angelhernandez@bkf.com

1. Common Plans of Development (subdivisions or contiguous, commonly owned lots, for the construction of two or more homes developed within 1 year of each other) are not considered single family projects by the MRP.
 2. Roadway projects creating 10,000 sq.ft. or more of contiguous impervious surface are subject to C.3 requirements if the roadway is new or being widened with additional traffic lanes.
 3. See Standard Industrial Classification (SIC) codes here: www.flowstobay.org/documents/business/new-development/Notice_to_Applicants-LID_FINAL.doc
 4. Project description examples: 5-story office building, industrial warehouse, residential with five 4-story buildings for 200 condominiums, etc.

I.B Is the project a “C.3 Regulated Project” per MRP Provision C.3.b?

I.B.1 Enter the amount of Impervious surface Retained, Replaced and/or Created by the project (use DMA Table):

Table I.B.1 Impervious⁵ and Pervious Surfaces (Match DMA Summary Table in Worksheet D, if applicable)

Type of Impervious Surface	I.B.1.a	I.B.1.b	I.B.1.c	I.B.1.d	I.B.1.e	
	Pre-Project Impervious Surface (sq.ft.)	Existing Impervious Surface to be Retained ⁶ (sq.ft.)	Existing Impervious Surface to be Replaced ⁶ (sq.ft.)	New Impervious Surface to be Created ⁶ (sq.ft.)	Post-Project Impervious Surface (sq.ft.) (=b+c+d)	
Roof area(s)	2973	2555	0	2980	5535	
Impervious ⁵ sidewalks, patios, paths, driveways, streets	8474	8333	0	5338	13671	
Impervious ⁵ uncovered parking ⁷					0	
Totals:	11447	10888	0	8318	19206	
I.B.1.f - Total Impervious Surface Replaced and Created: (sum of totals for columns I.B.1.c and I.B.1.d):			8318 sq. ft.			
Type of Pervious Surface	Pre-Project Pervious Surface (sq.ft.)				Post-project Pervious Surface (sq.ft.)	
Landscaping	125151				117392	
Pervious Pavement					I.B.1.e.1	
Green Roof						
Totals:	125151				117392	
Total Site Area (Total Impervious + Total Pervious)		136598				136598

I.B.2 Please review and attach additional worksheets as required below using the Total Impervious Surface (IS) Replaced and Created in cell **I.B.1.f** from Table **I.B.1** above and other factors:

	Review Steps	Check One		Attach Worksheet
		Yes	No	
I.B.2.a	Does this project involve any earthwork? If YES, then Check Yes, and Complete Worksheet A. If NO, then Check No, and go to I.B.2.b	<input checked="" type="checkbox"/>	<input type="checkbox"/>	A
I.B.2.b	Is I.B.1.f greater than or equal to 2,500 sq.ft? If YES, then the Project is subject to Provision C.3.i. - complete Worksheets B, C & go to I.B.2.c. If NO, go to I.B.2.i - or ask municipal staff for Small Project Checklist.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	B, C
I.B.2.c	Is the total Existing IS to be Replaced (column I.B.1.c) 50 percent or more of the total Pre-Project IS (column I.B.1.a)? If YES, site design, source control and treatment requirements apply to the whole site. Continue to I.B.2.d If NO, these requirements apply only to the impervious surface created and/or replaced. Continue to I.B.2.d	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
I.B.2.d	Is this project a Special Land Use Category (I.A.1) and is I.B.1.f greater than or equal to 5,000 sq.ft? If YES, project is a C.3 Regulated Project. Fill out Worksheet D. Then continue to I.B.2.f. If NO, go to I.B.2.e	<input type="checkbox"/>	<input checked="" type="checkbox"/>	D
I.B.2.e	Is I.B.1.f greater than or equal to 10,000 sq.ft? If YES, project is a C.3 Regulated Project - complete Worksheet D. Then continue to I.B.2.f. If NO, then skip to I.B.2.g.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	D
I.B.2.f	Is I.B.1.f greater than or equal to 43,560 sq.ft? If YES, project may be subject to Hydromodification Management requirements - complete Worksheet E then go to I.B.2.g. If NO, then go to I.B.2.g.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	E
I.B.2.g	Is I.A.3 greater than or equal to 1 acre? If YES, check box, obtain coverage under CA Construction General Permit & submit Notice of Intent to municipality - go to I.B.2.h. If NO, then go to I.B.2.h. For more information see: www.swrcb.ca.gov/water_issues/programs/stormwater/construction.shtml	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
I.B.2.h	Is this a Special Project or does it have the potential to be a Special Project? If YES, complete Worksheet F - then continue to I.B.2.i. If NO, go to I.B.2.i.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	F
I.B.2.i	Is project a Construction Stormwater Regulated Site (SWRS) ? 1) Sites that disturb 1 acre or more of land; 2) where the project requires a Grading Permit; 3) Sites with a) Residential new construction or a 50% or greater remodel, or b) Commercial/ Industrial construction of a new building or additions of 3,000 sq. ft. or greater, and with one or both of the following: (1) Sites where development will occur on a slope greater than or equal to 5:1 (20%), and/or (2) Sites where development will occur within 100 feet of a creek, wetland, or coastline; 4) Any public or private project involving work within a waterway; and 5) Sites within the ASBS watershed that involve soil disturbance. If NO, then go to I.B.2.j	<input type="checkbox"/>	<input checked="" type="checkbox"/>	G
I.B.2.j	For Municipal Staff Use Only: Are you using Alternative Certification for the project review? If YES, then fill out section G-1 on Worksheet G. Fill out other sections of Worksheet G as appropriate. See cell I.B.1.e.1 above - Is the project installing 3,000 square feet or more of pervious paving? If YES, then fill out section G-3 on Worksheet G. Add to Municipal Inspection Lists (C.3 and C.3.h)	<input type="checkbox"/>	<input type="checkbox"/>	G

5. Per the MRP, pavement that meets the following definition of pervious pavement is NOT an impervious surface. Pervious pavement is defined as pavement that stores and infiltrates rainfall at a rate equal to immediately surrounding unpaved, landscaped areas, or that stores and infiltrates the rainfall runoff volume described in Provision C.3.

6. “Retained” means to leave existing impervious surfaces in place; “Replaced” means to install new impervious surface where existing impervious surface is removed anywhere on the same property; and “Created” means the amount of new impervious surface being proposed which exceeds the total amount of existing impervious surface at the property.

7. Uncovered parking includes the top level of a parking structure.

Worksheet A

C.6 – Construction Stormwater BMPs

Identify Plan sheet showing the appropriate construction Best Management Practices (BMPs) used on this project:

(Applies to all projects with earthwork)

Yes	Plan Sheet	Best Management Practice (BMP)
<input checked="" type="checkbox"/>		Control and prevent the discharge of all potential pollutants, including pavement cutting wastes, paints, concrete, petroleum products, chemicals, wash water or sediments, rinse water from architectural copper, and non-stormwater discharges to storm drains and watercourses.
<input checked="" type="checkbox"/>		Store, handle, and dispose of construction materials/wastes properly to prevent contact with stormwater.
<input checked="" type="checkbox"/>		Do not clean, fuel, or maintain vehicles on-site, except in a designated area where wash water is contained and treated.
<input checked="" type="checkbox"/>		Train and provide instruction to all employees/subcontractors re: construction BMPs.
<input checked="" type="checkbox"/>		Protect all storm drain inlets in vicinity of site using sediment controls such as berms, fiber rolls, or filters.
<input checked="" type="checkbox"/>		Limit construction access routes and stabilize designated access points.
<input checked="" type="checkbox"/>		Attach the San Mateo Countywide Water Pollution Prevention Program's construction BMP plan sheet to project plans and require contractor to implement the applicable BMPs on the plan sheet.
<input checked="" type="checkbox"/>		Use temporary erosion controls to stabilize all denuded areas until permanent erosion controls are established.
<input checked="" type="checkbox"/>		Delineate with field markers clearing limits, easements, setbacks, sensitive or critical areas, buffer zones, trees, and drainage courses.
<input checked="" type="checkbox"/>		Provide notes, specifications, or attachments describing the following: <ul style="list-style-type: none"> ■ Construction, operation and maintenance of erosion and sediment controls, include inspection frequency; ■ Methods and schedule for grading, excavation, filling, clearing of vegetation, and storage and disposal of excavated or cleared material; ■ Specifications for vegetative cover & mulch, include methods and schedules for planting and fertilization; ■ Provisions for temporary and/or permanent irrigation.
<input checked="" type="checkbox"/>		Perform clearing and earth moving activities only during dry weather.
<input checked="" type="checkbox"/>		Use sediment controls or filtration to remove sediment when dewatering and obtain all necessary permits.
<input checked="" type="checkbox"/>		Trap sediment on-site, using BMPs such as sediment basins or traps, earthen dikes or berms, silt fences, check dams, soil blankets or mats, covers for soil stock piles, etc.
<input checked="" type="checkbox"/>		Divert on-site runoff around exposed areas; divert off-site runoff around the site (e.g., swales and dikes).
<input checked="" type="checkbox"/>		Protect adjacent properties and undisturbed areas from construction impacts using vegetative buffer strips, sediment barriers or filters, dikes, mulching, or other measures as appropriate.

Worksheet B

C.3 – Source Controls

Select appropriate source controls and identify the detail/plan sheet where these elements are shown.

Yes	Detail/Plan Sheet No.	Features that require source control measures	Source Control Measures (Refer to Local Source Control List for detailed requirements)
<input type="checkbox"/>		Storm Drain	Mark on-site inlets with the words "No Dumping! Flows to Bay" or equivalent.
<input type="checkbox"/>		Floor Drains	Plumb interior floor drains to sanitary sewer [or prohibit].
<input type="checkbox"/>		Parking garage	Plumb interior parking garage floor drains to sanitary sewer. ⁸
<input checked="" type="checkbox"/>		Landscaping	<ul style="list-style-type: none"> ■ Retain existing vegetation as practicable. ■ Select diverse species appropriate to the site. Include plants that are pest- and/or disease-resistant, drought-tolerant, and/or attract beneficial insects. ■ Minimize use of pesticides and quick-release fertilizers. ■ Use efficient irrigation system; design to minimize runoff.
<input type="checkbox"/>		Pool/Spa/Fountain	Provide connection to the sanitary sewer to facilitate draining. ⁸
<input type="checkbox"/>		Food Service Equipment (non-residential)	Provide sink or other area for equipment cleaning, which is: <ul style="list-style-type: none"> ■ Connected to a grease interceptor prior to sanitary sewer discharge.⁸ ■ Large enough for the largest mat or piece of equipment to be cleaned. ■ Indoors or in an outdoor roofed area designed to prevent stormwater run-on and run-off, and signed to require equipment washing in this area.
<input type="checkbox"/>		Refuse Areas	<ul style="list-style-type: none"> ■ Provide a roofed and enclosed area for dumpsters, recycling containers, etc., designed to prevent stormwater run-on and runoff. ■ Connect any drains in or beneath dumpsters, compactors, and tallow bin areas serving food service facilities to the sanitary sewer.⁸ ■ For more information, see the New Development Projects Litter Reduction Fact Sheet at: https://www.flowstobay.org/wp-content/uploads/2021/06/New-Dev-Litter-Reduction-Fact-Sheet-060421.pdf
<input type="checkbox"/>		Outdoor Process Activities ⁹	Perform process activities either indoors or in roofed outdoor area, designed to prevent stormwater run-on and runoff, and to drain to the sanitary sewer. ⁸
<input type="checkbox"/>		Outdoor Equipment/ Materials Storage	<ul style="list-style-type: none"> ■ Cover the area or design to avoid pollutant contact with stormwater runoff. ■ Locate area only on paved and contained areas. ■ Roof storage areas that will contain non-hazardous liquids, drain to sanitary sewer⁸, and contain by berms or similar.
<input type="checkbox"/>		Vehicle/ Equipment Cleaning	<ul style="list-style-type: none"> ■ Roofed, pave and berm wash area to prevent stormwater run-on and runoff, plumb to the sanitary sewer⁸, and sign as a designated wash area. ■ Commercial car wash facilities shall discharge to the sanitary sewer.⁸
<input type="checkbox"/>		Vehicle/ Equipment Repair and Maintenance	<ul style="list-style-type: none"> ■ Designate repair/maintenance area indoors, or an outdoors area designed to prevent stormwater run-on and runoff and provide secondary containment. Do not install drains in the secondary containment areas. ■ No floor drains unless pretreated prior to discharge to the sanitary sewer.⁸ ■ Connect containers or sinks used for parts cleaning to the sanitary sewer.⁸
<input type="checkbox"/>		Fuel Dispensing Areas	<ul style="list-style-type: none"> ■ Fueling areas shall have impermeable surface that is a) minimally graded to prevent ponding and b) separated from the rest of the site by a grade break. ■ Canopy shall extend at least 10 ft. in each direction from each pump and drain away from fueling area.
<input type="checkbox"/>		Loading Docks	<ul style="list-style-type: none"> ■ Cover and/or grade to minimize run-on to and runoff from the loading area. ■ Position downspouts to direct stormwater away from the loading area. ■ Drain water from loading dock areas to the sanitary sewer.⁸ ■ Install door skirts between the trailers and the building.
<input type="checkbox"/>		Fire Sprinklers	Design for discharge of fire sprinkler test water to landscape or sanitary sewer. ⁸
<input type="checkbox"/>		Miscellaneous Drain or Wash Water	<ul style="list-style-type: none"> ■ Drain condensate of air conditioning units to landscaping. Large air conditioning units may connect to the sanitary sewer.⁸ ■ Roof drains from equipment drain to landscaped area where practicable. ■ Drain boiler drain lines, roof top equipment, all wash water to sanitary sewer.⁸
<input type="checkbox"/>		Architectural Copper Rinse Water	Drain rinse water to landscaping, discharge to sanitary sewer ⁸ , or collect and dispose properly offsite. See flyer "Requirements for Architectural Copper."

8. Any connection to the sanitary sewer system is subject to sanitary district approval.

9. Businesses that may have outdoor process activities/equipment include machine shops, auto repair, industries with pretreatment facilities.

Worksheet C

Low Impact Development – Site Design Measures

Select Appropriate Site Design Measures (Required for C.3 Regulated Projects; all other projects are encouraged to implement site design measures, which may be required at municipality discretion.) Projects that create and/or replace 2,500 – 10,000 sq.ft. of impervious surface, and stand-alone single family homes that create/replace 2,500 sq.ft. or more of impervious surface, must include **one of Site Design Measures a through f** (Provision C.3.i requirements).¹⁰ Larger projects must also include applicable Site Design Measures g through i. Consult with municipal staff about requirements for your project.

Select appropriate site design measures and Identify the Plan Sheet where these elements are shown.

Yes	Plan Sheet Number	
<input type="checkbox"/>		a. Direct roof runoff into cisterns or rain barrels and use rainwater for irrigation or other non-potable use.
<input type="checkbox"/>		b. Direct roof runoff onto vegetated areas.
<input checked="" type="checkbox"/>		c. Direct runoff from sidewalks, walkways, and/or patios onto vegetated areas.
<input checked="" type="checkbox"/>		d. Direct runoff from driveways and/or uncovered parking lots onto vegetated areas.
<input type="checkbox"/>		e. Construct sidewalks, walkways, and/or patios with pervious or permeable surfaces. Use the specifications in the C3 Technical Guidance (Version 4.1) downloadable at www.flowstobay.org/newdevelopment .
<input type="checkbox"/>		f. Construct bike lanes, driveways, and/or uncovered parking lots with pervious surfaces. Use the specifications in the C3 Technical Guidance (Version 4.1) downloadable at www.flowstobay.org/newdevelopment .
<input type="checkbox"/>		g. Limit disturbance of natural water bodies and drainage systems; minimize compaction of highly permeable soils; protect slopes and channels; and minimize impacts from stormwater and urban runoff on the biological integrity of natural drainage systems and water bodies.
<input type="checkbox"/>		h. Conserve natural areas, including existing trees, other vegetation and soils.
<input checked="" type="checkbox"/>		i. Minimize impervious surfaces.

Regulated Projects can also consider the following site design measures to reduce treatment system sizing:

Yes	Plan Sheet Number	
<input type="checkbox"/>		j. Self-treating area (see Section 4.2 of the C.3 Technical Guidance)
<input type="checkbox"/>		k. Self-retaining area (see Section 4.3 of the C.3 Technical Guidance)
<input type="checkbox"/>		l. Plant or preserve interceptor trees (Section 4.1, C.3 Technical Guidance)

¹⁰ See MRP Provision C.3.a.i.(6) for non-C.3 Regulated Projects, C.3.c.i.(2)(a) for Regulated Projects, C.3.i for projects that create/replace 2,500 to 10,000 sq.ft. of impervious surface and stand-alone single family homes that create/replace 2,500 sq.ft. or more of impervious surface.

Worksheet D

C.3 Regulated Projects and Non-Regulated GI Projects

Stormwater Treatment Measures and Site Design Measures by Drainage Management Area (DMA)

Check all applicable boxes, answer questions and fill in cells related to the site design and treatment measure(s) included in the project.

Drainage Management Area Summary Table

Complete the information below at the Entitlement, Building Permit and Certificate of Occupancy stages for Regulated C.3 Projects and Non-Regulated Green Infrastructure Projects. (The first four cells are automatically filled in from the Project Info sheet.)

Project Name:	12400 Skyline Boulevard
Project Address:	12400 Skyline Boulevard, Woodside CA 94062
Cross Streets:	Misty Ridge Road
APN:	067-250-030

Special Project¹¹?	No	percent of C.3.d amount of runoff treated by Non-LID Systems on the Special Project site.
--------------------------------------	----	--

C.3 Regulated?	Yes
-----------------------	-----

Public or Private?	Private	Public projects are those on public property or ROW; private projects are on privately-owned property.
---------------------------	---------	--

DMA Identification Number	Impervious Area ¹² (ft ²)	Pervious Area ¹³ (ft ²)	Type of Site Design Measure or Treatment Measure ¹⁴	Sizing Criteria Used ¹⁵	Size Required ¹⁶	Size Provided
Example DMA 1	5,000	2,000	Bioretention unlined with underdrain	2c: Flow	208 sq.ft.	220 sq.ft.
Example DMA 2	1,000	1,000	Self-retaining area	Other	Less than 2:1 ratio	1:1 ratio
Example DMA 3	1,000	-	Infiltration trench	1b: Volume	1,000 cu.ft.	1,100 cu.ft.
Example DMA 4	1,000	-	Interceptor tree	Other	1 Tree per 200 sq.ft.	5 Trees
1	18,820	117778	-- Detention System	2a: Flow	1347 cu. ft.	1374 cu. ft
2			--	--		
3			--	--		
4			--	--		
5			--	--		
6			--	--		
7			--	--		
8			--	--		
9			--	--		
10			--	--		
11			--	--		
12			--	--		
13			--	--		
14			--	--		
15			--	--		
16			--	--		
TOTALS	18820	117778	N/A	N/A	N/A	N/A

Totals from Project Info Sheet Cells	19206	117392				
--------------------------------------	-------	--------	--	--	--	--

Is the project harvesting and using rainwater? Yes <input type="checkbox"/>	Rainwater Harvesting/Use Measures:
	<input type="checkbox"/> Rainwater Harvesting for indoor non-potable water use <input type="checkbox"/> Rainwater Harvesting for landscape irrigation use

A long term Operations and Maintenance (O&M) Agreement and Plan for this project will be required. Please contact the municipality for an agreement template and consult the C.3 Regulated Projects Guide at www.flowstobay.org for maintenance plan templates for specific facility types.

11. Special Projects are smart growth, high density, or transit-oriented developments with the criteria defined in Provision C.3.e.ii.(2), (3) or (4) (see Worksheet F).
 12. The sq.ft. of impervious area within the Drainage Management Area
 13. The sq.ft. of pervious area within the Drainage Management Area
 14. "Lined" refers to an impermeable liner placed on the bottom of a bioretention area, such that no infiltration into native soil occurs.
 15. Select from the menu which of the following Provision C.3.d.i hydraulic sizing methods was used, if any. Volume based approaches: 1(a) Urban Runoff Quality Management approach, or 1(b) 80% capture approach (recommended volume-based approach). Flow-based approaches: 2(a) 10% of 50-year peak flow approach, 2(b) 2 times the 85th percentile rainfall intensity approach, 2(c) 0.2-Inch-per-hour intensity approach (recommended flow-based approach - also known as the 4% rule), or 3 Combination flow and volume-based approach. "Other" is used for Site Design Measures such as Self-Retaining, Self-Treating Areas or Tree Interceptor Credits. Tree credits are 1/200 for evergreen or 1/100 for deciduous trees.
 16. Each DMA should drain to one treatment area (unless it is self-treating or self-retaining). If multiple DMAs are draining to one treatment area, they should be combined into one DMA. If one DMA drains to multiple treatment areas, that DMA should be split up so there is one DMA per treatment area (which allows the treatment area to be properly sized).

Worksheet E

Hydromodification Management

E-1 Is the project a Hydromodification Management¹⁴ (HM) Project?

E-1.1 Is the total impervious area increased over the pre-project condition?

- Yes. Continue to E-1.2.
- No. Go to Item E-1.3 and check "No".

E-1.2 Is the site located in an HM Control Area per the HM Control Areas map (Appendix H of the C.3 Technical Guidance)?

- Yes. Go to E-1.3 and check "Yes".
- No. Attach map, indicating project location. Go to Item E-1.3 and check "No".

E-1.3 Is the project a Hydromodification Management Project?

- Yes. The project is subject to HM requirements in Provision C.3.g of the Municipal Regional Stormwater Permit.
- No. The project is EXEMPT from HM requirements.

- If the project is subject to the HM requirements, incorporate in the project flow duration control measures designed such that post-project discharge rates and durations match pre-project discharge rates and durations.
- The Bay Area Hydrology Model (BAHM) has been developed to help size flow duration controls. See www.bayareahydrologymodel.org. Guidance is provided in Chapter 7 of the C.3 Technical Guidance.

E-2 Incorporate HM Controls (if required)

Are the applicable items provided with the Plans?

Yes	No	NA	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Site plans with pre- and post-project impervious surface areas, surface flow directions of entire site, locations of flow duration controls and site design measures per HM site design requirement
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Soils report or other site-specific document showing soil type(s) on site
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	If project uses the Bay Area Hydrology Model (BAHM), a list of model inputs and outputs.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	If project uses custom modeling, a summary of the modeling calculations with corresponding graph showing curve matching (existing, post-project, and post-project with HM controls curves), goodness of fit, and (allowable) low flow rate.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	If project uses the Impracticability Provision, a listing of all applicable costs and a brief description of the alternative HM project (name, location, date of start up, and entity responsible for maintenance).
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	If the project uses alternatives to the default BAHM approach or settings, a written description and rationale.

¹⁴ Hydromodification is the change in a site's runoff hydrograph, including increases in flows and durations that results when land is developed (made more impervious). The effects of hydromodification include, but are not limited to, increased bed and bank erosion of receiving streams, loss of habitat, increased sediment transport and/or deposition, and increased flooding. Hydromodification control measures are designed to reduce these effects.

Worksheet F Special Projects

Complete this worksheet for projects that appear to meet the definition of "Special Project", per Provision C.3.e.ii of the Municipal Regional Stormwater Permit (MRP). The form assists in determining whether a project meets Special Project criteria, and the percentage of low impact development (LID) treatment reduction credit. Special Projects that implement less than 100% LID treatment must provide a narrative discussion of the feasibility or infeasibility of 100% LID treatment. See Appendix J of the C.3 Technical Guidance Handbook (download at www.flowstobay.org) for more information.

F.1 "Special Project" Determination (Check the boxes to determine if the project meets any of the following categories.)

Special Project Category "A"

Does the project have ALL of the following characteristics?

- Located in a municipality's designated central business district, downtown core area or downtown core zoning district, neighborhood business district or comparable pedestrian-oriented commercial district, or historic preservation site and/or district¹⁵;
- Creates and/or replaces 0.5 acres or less of impervious surface;
- Includes no surface parking, except for incidental parking for emergency vehicle access, ADA access, and passenger or freight loading zones;
- Has at least 85% coverage of the entire site by permanent structures. The remaining 15% portion of the site may be used for safety access, parking structure entrances, trash and recycling service, utility access, pedestrian connections, public uses, landscaping and stormwater treatment.

No (continue) Yes – Complete Section F.2 below

Special Project Category "B"

Does the project have ALL of the following characteristics?

- Located in a municipality's designated central business district, downtown core area or downtown core zoning district, neighborhood business district or comparable pedestrian-oriented commercial district, or historic preservation site and/or district²⁰;
- Creates and/or replaces more than 0.5 acres of impervious area and less than 2.0 acres;
- Includes no surface parking, except for incidental parking for emergency access, ADA access, and passenger or freight loading zones;
- Has at least 85% coverage of the entire site by permanent structures. The remaining 15% portion of the site may be used for safety access, parking structure entrances, trash and recycling service, utility access, pedestrian connections, public uses, landscaping and stormwater treatment;
- Minimum density of either 50 dwelling units per acre (for residential projects) or a Floor Area Ratio (FAR) of 2:1 (for commercial projects) - mixed use projects may use either criterion. **Note Change on 7/1/16**¹⁶

No (continue) Yes – Complete Section F-2 below

Special Project Category "C"

Does the project have ALL of the following characteristics?

- At least 50% of the project area is within 1/2 mile of an existing or planned transit hub¹⁷ or 100% within a planned Priority Development Area¹⁸;
- The project is characterized as a non-auto-related use¹⁹; and
- Minimum density of either 25 dwelling units per acre (for residential projects) or a Floor Area Ratio (FAR) of 2:1 (for commercial projects) - mixed use projects may use either criterion. **Note Change on 7/1/16**¹⁶

No (continue) Yes – Complete Section F-2 below

¹⁵ And built as part of a municipality's stated objective to preserve/enhance a pedestrian-oriented type of urban design.

¹⁶ **Effective 7/1/16**, the MRP establishes definitions for "Gross Density"(GD) & FAR. GD is defined as, "the total number of residential units divided by the acreage of the entire site area, including land occupied by public right-of-ways, recreational, civic, commercial and other non-residential uses." FAR is defined as, "the Ratio of the total floor area on all floors of all buildings at a project site (except structures, floors, or floor areas dedicated to parking) to the total project site area.

¹⁷ "Transit hub" is defined as a rail, light rail, or commuter rail station, ferry terminal, or bus transfer station served by three or more bus routes. (A bus stop with no supporting services does not qualify.)

¹⁸ A "planned Priority Development Area" is an infill development area formally designated by the Association of Bay Area Government's / Metropolitan Transportation Commission's FOCUS regional planning program.

¹⁹ Category C specifically excludes stand-alone surface parking lots; car dealerships; auto and truck rental facilities with onsite surface storage; fast-food restaurants, banks or pharmacies with drive-through lanes; gas stations; car washes; auto repair and service facilities; or other auto-related project unrelated to the concept of transit oriented development.

F.2 LID Treatment Reduction Credit Calculation

(If more than one category applies, choose only one of the applicable categories and fill out the table for that category.)

Category	Impervious Area Created/Replaced (sq. ft.)	Site Coverage (%)	Project Density ¹⁶ or FAR ¹⁶	Density/Criteria	Allowable Credit (%)	Applied Credit (%)
A			N.A.	N.A.	100%	
B				Res ≥ 50 DU/ac or FAR ≥ 2:1	50%	
				Res ≥ 75 DU/ac or FAR ≥ 3:1	75%	
				Res ≥ 100 DU/ac or FAR ≥ 4:1	100%	
C				Location credit (select one)²⁰:		
				Within ¼ mile of transit hub	50%	
				Within ½ mile of transit hub	25%	
				Within a planned PDA	25%	
				Density credit (select one):		
				Res ≥ 30 DU/ac or FAR ≥ 2:1	10%	
				Res ≥ 60 DU/ac or FAR ≥ 4:1	20%	
				Res ≥ 100 DU/ac or FAR ≥ 6:1	30%	
				Parking credit (select one):		
				≤ 10% at-grade surface parking ²¹	10%	
No surface parking	20%					
TOTAL TOD CREDIT =					0	

F.3 Narrative Discussion of the Feasibility/Infeasibility of 100% LID Treatment:

If project will implement less than 100% LID, prepare a discussion of the feasibility or infeasibility of 100% LID treatment, as described in Appendix J of the C.3 Technical Guidance.

F.4 Select Certified Non-LID Treatment Measures:

If the project will include non-LID treatment measures, select a treatment measure certified for “Basic” General Use Level Designation (GULD) by the Washington State Department of Ecology’s Technical Assessment Protocol – Ecology (TAPE). Guidance is provided in Appendix J of the C.3 Technical Guidance (download at www.flowstobay.org).²²

²⁰ To qualify for the location credit, at least 50% of the project’s site must be located within the ¼ mile or ½ mile radius of an existing or planned transit hub, as defined on page 1, footnote 2. A planned transit hub is a station on the MTC’s Regional Transit Expansion Program list, per MTC’s Resolution 3434 (revised April 2006), which is a regional priority funding plan for future transit stations in the San Francisco Bay Area. To qualify for the PDA location credit, 100% of the project site must be located within a PDA, as defined on page 1, footnote 3.

²¹ The at-grade surface parking must be treated with LID treatment measures.

²² TAPE certification is used in order to satisfy Special Project’s reporting requirements in the MRP.

Worksheet G (For municipal staff use only)

G-1 Alternative Certification: Were the treatment and/or HM control sizing and design reviewed by a qualified third-party professional that is not a member of the project team or agency staff?

Yes No Name of Reviewer _____

G-2 Is project a Construction Stormwater Regulated Site (SWRS)? 1) Sites that disturb 1 acre or more of land; 2) where the project requires a Grading Permit; 3) Sites with a) Residential new construction or a 50% or greater remodel, or b) Commercial/ Industrial construction of a new building or additions of 3,000 sq. ft. or greater, and with one or both of the following: (1) Sites where development will occur on a slope greater than or equal to 5:1 (20%), and/or (2) Sites where development will occur within 100 feet of a creek, wetland, or coastline; 4) Any public or private project involving work within a waterway; and 5) Sites within the ASBS watershed that involve soil disturbance. These sites are subject to monthly inspections from Oct 1 to April 30. See MRP Provision C.6.e.ii.(2).

Yes No If yes, then add site to Staff's Monthly Rainy Season Construction Site Inspection List

G-3 Inspections of Sites with Pervious Paving: Starting 7/1/16, Regulated projects that are installing 3,000 sq.ft. or more of pervious paving (see cell **I.B.1.e.1**) (excluding private-use patios in single family homes, townhomes, or condominiums) must have the paving system inspected by the jurisdiction upon completion of the installation and the site must be added to the jurisdiction's list of sites needing inspections at least once every five years – see provision C.3.h. Pervious pavement systems include pervious concrete, pervious asphalt, pervious pavers and grid pavers etc. and are described in the C3 Technical Guidance (Version 4.1) downloadable at: www.flowstobay.org/newdevelopment.

Yes No If yes, then add site to Staff's Lists for Inspections at the end of Construction and O&M.

Operations and Maintenance (O&M) Submittals

G-4 Stormwater Treatment Measure and/HM Control Owner or Operator's Information:

Name: _____

Address: _____

Phone: _____ Email: _____

- Applicant must call for inspection and receive inspection within 45 days of installation of treatment measures and/or hydromodification management controls.

The following questions apply to C.3 Regulated Projects and Hydromodification Management Projects.

	Yes	No	N/A
G-4.1 Was maintenance plan submitted?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G-4.2 Was maintenance plan approved?	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G-4.3 Was maintenance agreement submitted? (Date executed: _____)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

- Attach the executed maintenance agreement as an appendix to this checklist.

G-5 Annual Operations and Maintenance (O&M) Submittals (for municipal staff use only):

For C.3 Regulated Projects and Hydromodification Management Projects, indicate the dates on which the Applicant submitted annual reports for project O&M:

G-6 Comments (for municipal staff use only):

G-7 NOTES (for municipal staff use only):

Section I Notes: _____
Worksheet A Notes: _____
Worksheet B Notes: _____
Worksheet C Notes: _____
Worksheet D Notes: _____
Worksheet E Notes: _____
Worksheet F Notes: _____

G-8 Project Close-Out (for municipal staff use only):

	Yes	No	NA
8.1 Were final Conditions of Approval met?	<input type="checkbox"/>	<input type="checkbox"/>	
8.2 Was initial inspection of the completed treatment/HM measure(s) conducted? (Date of inspection: _____)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8.3 Was maintenance plan submitted? (Date executed: _____)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8.4 Was project information provided to staff responsible for O&M verification inspections? (Date provided to inspection staff: _____)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

G-9 Project Close-Out (Continued – for municipal staff use only):

Name of staff confirming project is closed out: _____
Signature: _____ Date: _____
Name of O&M staff receiving information: _____
Signature: _____ Date: _____